



## 280 Remington (7mm Remington Express)

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	3.200"	3.200"	3.265"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 4350	Remington	CCI 200	50.0	2691	52.0	2854
Alliant Reloder 26	Federal	Federal 210	49.9	2625	55.0 C	2841
Hodgdon H4350	Remington	CCI 200	47.0	2571	51.0	2828
Alliant Reloder 19	Remington	CCI 200	53.0	2658	55.0	2813
IMR 4831	Remington	CCI 200	52.0	2686	54.0	2808
Alliant Reloder 22	Remington	CCI 200	54.0	2707	56.0	2807
Alliant Reloder 23	Federal	Federal 210	48.8	2584	54.2 C	2795
IMR 4350	Remington	CCI 200	49.0	2522	53.0	2791
Hodgdon H4831SC	Remington	CCI 200	53.0	2697	55.0	2773
Alliant Reloder 17	Federal	Federal 210	45.7	2538	50.6	2773
Alliant Power Pro 4000-MR	Federal	Federal 210	46.3	2530	51.4	2769
Alliant Reloder 16	Federal	Federal 210	45.2	2564	50.0	2758
IMR 7828	Remington	CCI 200	55.0	2654	57.0	2743
Accurate 3100	Remington	CCI 200	53.0	2637	55.0 C	2725
Ramshot Hunter	Federal	Federal 210	45.9	2491	50.7	2711
IMR 4064	Remington	CCI 200	41.0	2492	45.0	2677
Hodgdon H414	Remington	CCI 250	44.0	2468	48.0	2631
IMR 4895	Remington	CCI 200	39.0	2412	43.0	2624
IMR SR 4759 (reduced load)	Remington	CCI 200	22.0	1711	26.0	2008

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load