



280 Remington (7mm Remington Express)

.284"	7mm Grand Slam® SP/CANN
Weight (grains)	175
Ballistic Coefficient	0.436
Sectional Density	0.310
COAL Tested	3.260"
Speer Part No.	1643

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Ramshot Magnum	Federal	Federal 210	55.5	2485	61.5	2729
Alliant Reloder 26	Federal	Federal 210	50.4	2477	55.5	2723
Alliant Reloder 23	Federal	Federal 210	49.1	2450	54.2 C	2671
Vihavuori N560	Remington	CCI 200	50.0	2567	52.0	2644
Alliant Power Pro 4000-MR	Federal	Federal 210	46.4	2384	51.4	2639
Alliant Reloder 17	Federal	Federal 210	45.2	2363	50.2	2638
Alliant Reloder 16	Federal	Federal 210	45.6	2417	50.4	2627
Alliant Reloder 22	Remington	CCI 200	51.0	2520	53.0	2616
Hodgdon H1000	Remington	CCI 200	53.0	2434	57.0 C	2615
Alliant Reloder 19	Remington	CCI 200	48.0	2420	52.0	2597
IMR 4350	Remington	CCI 200	45.0	2338	49.0	2578
IMR 4831	Remington	CCI 200	48.0	2479	50.0	2570
IMR 7828	Remington	CCI 200	51.0	2465	53.0	2568
Hodgdon H4831SC	Remington	CCI 200	50.0	2454	52.0	2558
Hodgdon H4350	Remington	CCI 200	43.0	2388	47.0	2555
Accurate 3100	Remington	CCI 200	49.0	2416	51.0	2520
Hodgdon H414	Remington	CCI 250	44.0	2401	46.0	2461
Winchester 760	Remington	CCI 250	44.0	2370	46.0	2452
IMR SR 4759 (reduced load)	Remington	CCI 200	21.0	1490	25.0	1753

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load