



30-06 Springfield

.308"	30
Weight (grains)	Plinker® SPRN
Ballistic Coefficient	100
Sectional Density	0.144
COAL Tested	0.151
Speer Part No.	2.935"
	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 3031	Winchester	CCI 200	53.0	3251	57.0	3510
IMR 4064	Winchester	CCI 200	55.0	3202	59.0	3450
Hodgdon H335	Winchester	CCI 250	54.0	3147	58.0	3383
Winchester 748	Winchester	CCI 250	56.0	3166	60.0	3369
IMR 4895	Winchester	CCI 200	51.0	3073	55.0	3323
IMR 4320	Winchester	CCI 200	54.0	3044	58.0	3289
Hodgdon H322	Winchester	CCI 200	48.0	2985	52.0	3268
Alliant Reloder 7	Winchester	CCI 200	43.0	2875	47.0	3239
IMR SR 4759 (reduced load)	Winchester	CCI 200	16.0	1545	20.0	1969

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load