



30-06 Springfield

	30
	TNT® HP
Weight (grains)	125
Ballistic Coefficient	0.341
Sectional Density	0.188
COAL Tested	3.100"
Speer Part No.	1986

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	48.6	3037	53.7	3261
Alliant Power Pro Varmint	Federal	Federal 210	48.4	2964	53.6	3228
IMR 8208 XBR	Federal	Federal 210	48.4	3048	52.6	3222
Alliant Reloder 10X	Federal	Federal 210	46.3	2959	51.3	3210
Accurate 2460	Winchester	CCI 250	49.0	2974	53.0	3178
IMR 3031	Winchester	CCI 200	50.0	2862	54.0	3167
Vihtavuori N135	Winchester	CCI 200	49.0	2844	53.0	3116
Accurate 2015	Winchester	CCI 200	46.0	2905	50.0	3111
Hodgdon BL-C(2)	Winchester	CCI 250	51.0	2874	55.0	3106
Accurate 2495	Winchester	CCI 200	50.0	2876	54.0	3105
Accurate 2230	Winchester	CCI 200	47.0	2887	51.0	3103
Hodgdon H335	Winchester	CCI 250	51.0	2872	55.0	3093
Accurate 2520	Winchester	CCI 250	48.0	2867	52.0	3085
Hodgdon Varget	Winchester	CCI 200	51.5	2763	55.5	3037
Hodgdon H4895	Winchester	CCI 200	47.0	2741	51.0	3025
Alliant Power Pro 1200-R	Federal	Federal 210	38.5	2812	42.5	3025
IMR 4320	Winchester	CCI 200	51.0	2762	55.0	3011
IMR 4895	Winchester	CCI 200	48.0	2777	52.0	3002
Hodgdon H322	Winchester	CCI 200	44.0	2720	48.0	2916

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load