



30-06 Springfield

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	3.250"	3.250"	3.165"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Ramshot Hunter	Federal	Federal 210	57.4	2803	63.4 C	2974
Alliant Power Pro 4000-MR	Federal	Federal 210	54.8	2705	60.8 C	2943
Alliant Reloder 16	Federal	Federal 210	52.0	2733	57.0 C	2936
Alliant Reloder 17	Federal	Federal 210	51.9	2678	56.5	2879
Accurate 4350	Federal	Federal 210	53.6	2622	59.5 C	2870
Alliant Power Pro 2000-MR	Federal	Federal 210	47.2	2628	52.2	2851
Winchester 760	Winchester	CCI 250	53.0	2631	57.0	2840
Hodgdon H4831SC	Winchester	CCI 200	60.0	2534	62.0 C	2808
IMR 4350	Winchester	CCI 200	54.0	2501	58.0	2782
Vihtavuori N540	Winchester	CCI 200	43.0	2598	47.0	2774
Alliant Reloder 22	Winchester	CCI 200	58.0	2530	62.0 C	2759
Hodgdon H4350	Winchester	CCI 200	54.0	2489	58.0 C	2758
Hodgdon H414	Winchester	CCI 250	52.0	2520	56.0	2757
Hodgdon H380	Winchester	CCI 250	51.0	2544	55.0	2740
Hodgdon Varget	Winchester	CCI 200	46.0	2462	50.0	2703
IMR 4831	Winchester	CCI 200	55.0	2442	59.0	2702
Vihtavuori N140	Winchester	CCI 200	46.0	2490	50.0	2695
IMR 4064	Winchester	CCI 200	46.5	2433	50.5	2671
Alliant Reloder 19	Winchester	CCI 200	55.0	2372	59.0 C	2644
Accurate 2520	Winchester	CCI 250	42.0	2354	46.0	2624
IMR SR 4759 (reduced load)	Winchester	CCI 200	21.0	1615	25.0	1949

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load