



30-06 Springfield

.308"	30
	Match BTHP
Weight (grains)	168
Ballistic Coefficient	0.534
Sectional Density	0.253
COAL Tested	3.295"
Speer Part No.	2040

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	52.9	2725	58.6 C	2952
Alliant Reloder 17	Federal	Federal 210	51.0	2626	56.7	2886
Vihtavuori N160	Winchester	CCI 200	57.0	2610	61.0	2863
IMR 4451	Federal	Federal 210	52.3	2633	58.1 C	2857
Hodgdon H4350	Winchester	CCI 200	56.0	2591	60.0 C	2831
IMR 4350	Winchester	CCI 200	55.0	2586	59.0	2818
Alliant AR-Comp	Federal	Federal 210	43.1	2590	47.7	2787
†Hodgdon H380	Winchester	CCI 250	51.0	2479	55.0	2770
IMR 7828	Winchester	CCI 250	58.0	2575	62.0	2739
Alliant Reloder 19	Winchester	CCI 200	57.0	2489	61.0 C	2730
Hodgdon H4831	Winchester	CCI 250	57.0	2450	61.0 C	2693
IMR 4831	Winchester	CCI 250	56.0	2398	60.0	2664
Hodgdon H414	Winchester	CCI 250	50.0	2453	54.0	2664
Winchester 760	Winchester	CCI 250	50.0	2411	54.0	2658
†IMR 4895	Winchester	CCI 200	44.0	2461	48.0	2635
†IMR 4064	Winchester	CCI 200	45.0	2389	49.0	2577

†—denotes propellant suitable for gas-operated semi-auto match rifles

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load