



## 30-378 Weatherby Magnum

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.430"	3.600"	3.600"	3.645"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Weatherby	CCI 250	107.5	3348	<b>113.5</b>	3608
IMR 7977	Weatherby	CCI 250	111.5	3323	<b>118.1</b>	3569
Accurate 3100	Weatherby	CCI 250	100.0	3269	<b>104.0</b>	3414
IMR 4831	Weatherby	CCI 250	96.0	3279	<b>100.0</b>	3406
Accurate 4350	Weatherby	CCI 250	97.0	3272	<b>101.0</b>	3405
Alliant Reloder 19	Weatherby	CCI 250	101.0	3308	<b>105.0</b>	3404
IMR 4350	Weatherby	CCI 250	93.0	3248	<b>97.0</b>	3385
Hodgdon H1000	Weatherby	CCI 250	108.0	3236	<b>112.0</b>	3364
Hodgdon H4350	Weatherby	CCI 250	90.0	3187	<b>94.0</b>	3317
Hodgdon H4831SC	Weatherby	CCI 250	97.0	3185	<b>101.0</b>	3305

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*