



30-378 Weatherby Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN	30 Match BTSP
Weight (grains)	165	165	165	168
Ballistic Coefficient	0.520	0.444	0.354	0.534
Sectional Density	0.248	0.248	0.248	0.253
COAL Tested	3.645"	3.645"	3.645"	3.645"
Speer Part No.	2034	2035	2038	2040

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Weatherby	CCI 250	104.0	3162	110.5	3435
IMR 7977	Weatherby	CCI 250	108.0	3186	114.6	3430
Alliant Reloder 19	Weatherby	CCI 250	99.0	3185	103.0	3285
IMR 4831	Weatherby	CCI 250	94.0	3162	98.0	3284
Accurate 3100	Weatherby	CCI 250	97.0	3129	101.0	3268
IMR 7828	Weatherby	CCI 250	104.0	3200	106.0	3267
Hodgdon H1000	Weatherby	CCI 250	103.0	3125	109.0	3249
IMR 4350	Weatherby	CCI 250	92.0	3093	96.0	3223
Hodgdon H4831SC	Weatherby	CCI 250	95.0	3071	99.0	3187

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load