



30-378 Weatherby Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.645"	3.645"	3.645"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 7977	Weatherby	CCI 250	106.5	3067	113.7	3334
Hodgdon H870	Weatherby	CCI 250	119.0	3147	123.0 C	3249
Accurate 8700	Weatherby	CCI 250	115.0	3080	119.0	3206
Alliant Reloder 26	Weatherby	CCI 250	99.5	2968	105.0	3190
IMR 7828	Weatherby	CCI 250	96.0	3062	100.0	3189
IMR 4831	Weatherby	CCI 250	91.0	3041	95.0	3161
Hodgdon H50BMG	Weatherby	CCI 250	114.0	3019	118.0 C	3137
Hodgdon H1000	Weatherby	CCI 250	102.0	3029	106.0	3134
Accurate 3100	Weatherby	CCI 250	94.0	2996	98.0	3121
Hodgdon H4831SC	Weatherby	CCI 250	92.0	2945	96.0	3069
Vihtavuori N170	Weatherby	CCI 250	93.0	2957	97.0	3057

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load