



30-378 Weatherby Magnum

.308"	30
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	3.645 "
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H870	Weatherby	CCI 250	114.0	2973	118.0 C	3088
Accurate 8700	Weatherby	CCI 250	112.0	2952	116.0 C	3074
Alliant Reloder 26	Weatherby	CCI 250	96.0	2852	103.0	3073
IMR 7977	Weatherby	CCI 250	100.0	2803	106.0	3049
Hodgdon H50BMG	Weatherby	CCI 250	112.0	2930	116.0 C	3036
Accurate 3100	Weatherby	CCI 250	92.0	2889	96.0	3012
IMR 7828	Weatherby	CCI 250	93.0	2941	95.0	3002
Hodgdon H1000	Weatherby	CCI 250	99.0	2884	103.0	2994

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load