



300 Holland & Holland Magnum

.308"	30
	Plinker® SPRN
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	3.260"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	Federal 215	66.6	3463	73.8	3757
Alliant AR-Comp	Federal	Federal 215	60.9	3323	67.5	3691
IMR 4166	Federal	Federal 215	57.0	3170	63.1	3514
Alliant Reloder 10X	Federal	Federal 215	52.2	3349	55.7	3485
IMR 4895	Winchester	CCI 200	54.0	3098	58.0	3308
IMR 4064	Winchester	CCI 200	52.0	2930	56.0	3143
IMR 4320	Winchester	CCI 200	52.0	2716	56.0	2994
Hodgdon H380	Winchester	CCI 250	54.0	2776	58.0	2985
IMR 3031	Winchester	CCI 200	47.0	2723	51.0	2933
IMR 4198	Winchester	CCI 200	39.0	2562	43.0	2866
Winchester 748	Winchester	CCI 250	51.0	2624	55.0	2861
IMR 4350	Winchester	CCI 200	54.0	2574	58.0	2772
IMR SR 4759 (reduced load)	Winchester	CCI 200	21.0	1670	23.0	1839

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load