



300 Holland & Holland Magnum

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.365"	3.500"	3.500"	3.515"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	70.3	2954	77.9	3276
IMR 4831	Winchester	CCI 200	69.0	3084	73.0	3265
IMR 4350	Winchester	CCI 200	66.0	3051	70.0	3239
Alliant Power Pro 4000-MR	Federal	Federal 215	65.8	2947	72.8	3218
Alliant Reloder 16	Federal	Federal 215	63.2	2900	70.1	3208
Alliant Reloder 23	Federal	Federal 215	67.5	2921	74.7	3203
Alliant Reloder 17	Federal	Federal 215	61.7	2968	68.4	3194
Alliant Reloder 19	Winchester	CCI 250	68.0	2960	72.0	3170
Vihtavuori N165	Winchester	CCI 250	69.0	2941	73.0	3127
IMR 4064	Winchester	CCI 200	57.0	2902	61.0	3109
Accurate 3100	Winchester	CCI 250	68.0	2920	72.0	3092
Accurate 4350	Winchester	CCI 250	64.0	2886	68.0	3065
IMR 3031	Winchester	CCI 200	52.0	2926	56.0	3054
IMR 4895	Winchester	CCI 200	53.0	2703	57.0	2949
IMR 4320	Winchester	CCI 200	52.0	2642	56.0	2877
Hodgdon H380	Winchester	CCI 250	57.0	2620	61.0	2873
IMR SR 4759 (reduced load)	Winchester	CCI 200	25.0	1791	27.0	1934

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load