



## 300 Remington Ultra Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.411	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.600"	3.600"	3.460"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 33	Federal	Federal 215	93.4	2863	<b>103.4</b>	3209
Alliant Reloder 26	Federal	Federal 215	79.5	2849	<b>88.3</b>	3168
Alliant Reloder 25	Federal	Federal 215	90.0	3021	<b>94.0</b>	3146
IMR 7977	Federal	Federal 215	83.9	2847	<b>93.2</b>	3144
Alliant Reloder 23	Federal	Federal 215	77.3	2861	<b>85.8</b>	3128
Ramshot Magnum	Federal	Federal 215	93.0	3001	<b>97.0</b>	3119
Alliant Reloder 22	Federal	Federal 215	86.0	2997	<b>90.0</b>	3118
Hodgdon Retumbo	Federal	Federal 215	90.0	2981	<b>94.0</b>	3099
IMR 7828	Federal	Federal 215	85.0	2961	<b>89.0</b>	3095
Vihtavuori N560	Federal	Federal 215	82.0	2961	<b>86.0</b>	3077
Accurate 3100	Federal	Federal 215	81.0	2931	<b>85.0</b>	3047
Hodgdon H1000	Federal	Federal 215	90.0	2937	<b>94.0</b>	3043
Accurate MagPro	Federal	Federal 215	84.0	2896	<b>88.0</b>	2996

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*