



300 Remington Ultra Magnum

.308"	30
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	3.600"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon US 869	Federal	Federal 215	100.0	2889	104.0	3000
Alliant Reloder 33	Federal	Federal 215	83.9	2736	92.9	2998
Alliant Reloder 50	Federal	Federal 215	86.8	2733	95.6	2983
Accurate 8700	Federal	Federal 215	100.0	2896	104.0 C	2962
hodgdon Retumbo	Federal	Federal 215	86.0	2842	90.0	2949
Alliant Reloder 25	Federal	Federal 215	84.0	2837	88.0	2942
Alliant Reloder 26	Federal	Federal 215	72.9	2727	80.2	2939
Alliant Reloder 22	Federal	Federal 215	82.0	2829	86.0	2936
Ramshot Magnum	Federal	Federal 215	88.0	2825	92.0	2933
IMR 7828	Federal	Federal 215	81.0	2781	85.0	2915
Viitavuori N560	Federal	Federal 215	78.0	2789	82.0	2903
IMR 7977	Federal	Federal 215	76.3	2652	84.7	2900
Alliant Reloder 23	Federal	Federal 215	69.7	2672	76.3	2863
Accurate MagPro	Federal	Federal 215	79.0	2714	83.0	2821

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load