



300 Ruger Compact Magnum

.308"	30 HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	2.780"
Speer Part No.	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Hornady	CCI 250	60.5	3006	67.0 C	3304
Alliant Power Pro 2000-MR	Hornady	CCI 250	57.5	3036	63.5	3303
Alliant Reloder 17	Hornady	CCI 250	58.2	2969	64.5	3295
Hodgdon H414	Hornady	CCI 250	58.0	2971	64.1	3261
Accurate 4350	Hornady	CCI 250	61.4	2931	68.0 C	3259
Alliant Reloder 15	Hornady	CCI 250	54.2	2961	60.2	3256
Vihtavuori N550	Hornady	CCI 250	56.2	2930	62.4	3254
Hodgdon Varget	Hornady	CCI 250	52.9	3028	58.0	3218
IMR 4451	Hornady	CCI 250	58.4	2889	64.8	3195

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load