



300 Ruger Compact Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot- Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.840"	2.840"	2.820"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon SUPERFORMANCE	Hornady	CCI 250	60.5	2790	66.9	3047
Alliant Power Pro 4000-MR	Hornady	CCI 250	60.2	2787	66.6 C	3035
Alliant Reloder 19	Hornady	CCI 250	62.3	2724	69.2 C	3027
Ramshot Hunter	Hornady	CCI 250	62.0	2840	66.8	3021
Alliant Reloder 16	Hornady	CCI 250	57.0	2715	63.2 C	3008
Alliant Reloder 17	Hornady	CCI 250	54.5	2671	60.5	2969
Hodgdon Hybrid 100V	Hornady	CCI 250	55.3	2726	61.3	2968
Vihtavuori N550	Hornady	CCI 250	53.3	2666	59.3	2952
Winchester 760	Hornady	CCI 250	54.8	2683	61.0	2948
IMR 4831	Hornady	CCI 250	58.2	2605	64.6	2896

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load