



300 Savage

.308"	30
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	2.475"
Speer Part No.	1805

Plinker® SPRN

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	Federal	CCI 250	44.0	2901	48.0 C	3192
Alliant Reloder 7	Federal	CCI 200	36.0	2795	40.0	3154
Accurate 2230	Federal	CCI 250	41.0	2771	45.0	3096
IMR 4064	Federal	CCI 200	42.0	2791	46.0 C	3091
IMR 3031	Federal	CCI 200	39.0	2778	43.0 C	3091
IMR 4895	Federal	CCI 200	41.0	2777	45.0 C	3053
Vihtavuori N130	Federal	CCI 200	36.0	3032	40.0	3032
IMR 4320	Federal	CCI 200	41.0	2678	45.0 C	2924
IMR 4350	Federal	CCI 200	42.0	2345	46.0 C	2593
IMR SR 4759 (reduced load)	Federal	CCI 200	16.0	1676	18.0	1911

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load