



## 300 Savage

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	2.550"	2.550"	2.535"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	CCI 200	39.0	2314	<b>43.0 C</b>	2519
Vihtavuori N140	Federal	CCI 200	38.0	2262	<b>42.0 C</b>	2512
IMR 4350	Federal	CCI 200	41.0	2175	<b>45.0 C</b>	2413
Hodgdon H414	Federal	CCI 250	41.0	2164	<b>45.0 C</b>	2412
Winchester 760	Federal	CCI 250	40.5	2152	<b>44.5 C</b>	2395
Hodgdon H380	Federal	CCI 250	40.0	2156	<b>44.0 C</b>	2389
Winchester 748	Federal	CCI 250	36.0	2115	<b>40.0</b>	2372
IMR 4895	Federal	CCI 200	34.0	2103	<b>38.0</b>	2367
IMR 4064	Federal	CCI 200	35.0	2120	<b>39.0</b>	2355
Accurate 2700	Federal	CCI 250	38.0	2056	<b>42.0 C</b>	2278
IMR 4198 (reduced load)	Federal	CCI 200	20.0	1585	<b>24.0</b>	1747

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*