



300 Savage

.308"	30 Spitzer SP Hot- Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	2.550"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	CCI 200	38.0	2042	42.0 C	2423
Vihtavuori N140	Federal	CCI 200	36.0	2017	40.0 C	2301
Hodgdon H414	Federal	CCI 250	41.0	2049	45.0 C	2285
IMR 4350	Federal	CCI 200	39.0	2031	43.0 C	2245
IMR 4064	Federal	CCI 200	32.0	1913	36.0	2166
Hodgdon H380	Federal	CCI 250	37.0	1914	41.0 C	2156
Winchester 760	Federal	CCI 250	37.0	1931	41.0 C	2156
Winchester 748	Federal	CCI 250	33.0	1902	37.0	2151
Accurate 2700	Federal	CCI 250	36.0	1929	40.0 C	2130
IMR 4895	Federal	CCI 200	31.0	1874	35.0	2118
IMR 4198 (reduced load)	Federal	CCI 200	22.0	1585	24.0	1747

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load