



300 Winchester Magnum

.308"	30
	GD
Weight (grains)	168
Ballistic Coefficient	0.572
Sectional Density	0.253
COAL Tested	3.340"
Speer Part No.	308168GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	70.5	2806	78.1	3167
Alliant Reloder 19	Federal	Federal 215	70.4	2771	78.0 C	3132
Alliant Power Pro 4000-MR	Federal	Federal 215	66.1	2847	73.5	3123
Alliant Reloder 22	Federal	Federal 215	68.7	2808	76.1	3115
Vihtavuori N560	Federal	Federal 215	70.2	2797	77.6	3114
IMR 7828	Federal	Federal 215	70.4	2781	78.2 C	3109
Alliant Reloder 23	Federal	Federal 215	68.6	2813	76.1 C	3103
Alliant Reloder 16	Federal	Federal 215	63.7	2815	70.9	3101
Accurate 4350	Federal	Federal 215	66.5	2774	73.8	3095
Alliant Reloder 17	Federal	Federal 215	60.9	2836	67.5	3076
Hodgdon H1000	Federal	Federal 215	74.1	2819	82.0 C	3066
Hodgdon H4831SC	Federal	Federal 215	67.1	2830	74.3	3050
Hodgdon H4350	Federal	Federal 215	61.2	2827	68.0	3038
Ramshot Hunter	Federal	Federal 215	63.8	2779	70.8	3038

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load