



300 Winchester Short Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.810"	2.810"	2.780"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	65.5	2875	72.6 C	3191
IMR 7828	Winchester	CCI 200	71.0 C	3019	75.0 C	3167
Vihtavuori N560	Winchester	CCI 200	70.0	3012	74.0 C	3151
Accurate 4350	Winchester	CCI 200	66.0	2968	70.0 C	3138
Alliant Reloder 19	Winchester	CCI 200	69.0	2983	73.0 C	3135
Alliant Power Pro 4000-MR	Federal	Federal 215	62.1	2852	68.7	3133
IMR 4831	Winchester	CCI 200	66.5	2984	70.5 C	3131
Alliant Reloder 22	Winchester	CCI 200	69.0	2978	73.0 C	3126
Alliant Reloder 23	Federal	Federal 215	64.2	2860	71.2 C	3124
Alliant Reloder 17	Federal	Federal 215	59.3	2845	65.5	3115
Alliant Reloder 16	Federal	Federal 215	59.8	2870	66.1	3114
IMR 4350	Winchester	CCI 200	64.5	2932	68.5	3103
Hodgdon H414	Winchester	CCI 250	63.5	2961	67.5 C	3099
Winchester 760	Winchester	CCI 250	64.0	2968	68.0	3097
Accurate 3100	Winchester	CCI 200	71.0	2979	73.0 C	3075
Hodgdon H4350	Winchester	CCI 200	61.0	2944	65.0	3073
Hodgdon H4831SC	Winchester	CCI 200	68.5	2925	72.5 C	3062

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load