



speer®
bullets

303 British

.311"	303
	SPRN Hot-Cor®
Weight (grains)	180
Ballistic Coefficient	0.299
Sectional Density	0.266
COAL Tested	3.075"
Speer Part No.	2223

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Federal	CCI 215	44.0	2351	48.0	2514
Vihtavuori N540	Federal	CCI 210	40.0	2303	44.0	2497
Alliant Reloder 15	Federal	CCI 210	38.0	2274	42.0	2479
Ramshot Big Game	Federal	CCI 215	41.0	2316	45.0	2471
IMR 4895	Federal	CCI 210	37.0	2212	41.0	2420
Hodgdon Varget	Federal	CCI 210	37.0	2238	41.0	2408
IMR 4350	Federal	CCI 210	43.0	2181	47.0 C	2389
Accurate XMR 4064	Federal	CCI 210	35.0	2128	39.0	2339
Alliant Reloder 10X	Federal	CCI 210	30.5	2125	34.5	2324
Hodgdon H322	Federal	CCI 210	31.5	2122	35.5	2320
Accurate XMP 5744 (reduced load)	Federal	CCI 210	27.0	1956	29.0	2076

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load