



307 Winchester

.308"	30 HP
Weight (grains)	110
Ballistic Coefficient	0.128
Sectional Density	0.166
COAL Tested	2.390"
Speer Part No.	1835

NOTE: COAL less than minimum. We recommend single loading into the chamber.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	35.0	2540	39.0	2868
IMR 4198	Winchester	CCI 200	33.0	2504	37.0	2860
Hodgdon H322	Winchester	CCI 200	39.0	2511	41.0	2857
IMR 4895	Winchester	CCI 200	40.0	2599	44.0 C	2806
IMR 3031	Winchester	CCI 200	39.0	2257	43.0	2767
IMR 4064	Winchester	CCI 200	41.0	2383	45.0	2750
Winchester 748	Winchester	CCI 250	42.0	2448	46.0	2748
Alliant 2400	Winchester	CCI 200	22.0	2279	26.0	2585

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load