



307 Winchester

.308"	30
	SPFN Hot-Cor®
Weight (grains)	130
Ballistic Coefficient	0.213
Sectional Density	0.196
COAL Tested	2.530"
Speer Part No.	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Winchester	CCI 200	41.0	2803	45.8	3030
IMR 8208 XBR	Winchester	CCI 200	42.5	2780	45.8	2985
Hodgdon BL-C(2)	Winchester	CCI 250	46.0	2713	50.0 C	2971
Winchester 748	Winchester	CCI 250	45.0	2631	49.0 C	2926
Hodgdon H335	Winchester	CCI 250	41.0	2618	45.0	2875
IMR 4166	Winchester	CCI 200	40.0	2593	45.5	2874
IMR 4895	Winchester	CCI 200	41.0	2509	45.0	2857
IMR 3031	Winchester	CCI 200	39.0	2340	43.0 C	2736
IMR 4064	Winchester	CCI 200	41.0	2335	45.0 C	2730
Hodgdon H322	Winchester	CCI 200	36.0	2243	40.0	2696
Alliant Reloder 7	Winchester	CCI 200	33.0	2249	37.0	2623
IMR 4320	Winchester	CCI 200	39.0	2237	43.0	2622

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load