



## 307 Winchester

<b>.308"</b>	<b>30</b>
	<b>SPFN Hot-Cor®</b>
<b>Weight (grains)</b>	150
<b>Ballistic Coefficient</b>	0.255
<b>Sectional Density</b>	0.226
<b>COAL Tested</b>	2.530"
<b>Speer Part No.</b>	2011

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Winchester	CCI 200	41.0	2672	<b>44.6</b>	2831
IMR 8208 XBR	Winchester	CCI 200	40.5	2615	<b>43.8</b>	2793
IMR 4166	Winchester	CCI 200	40.5	2530	<b>43.8</b>	2691
Winchester 748	Winchester	CCI 250	41.0	2501	<b>45.0</b>	2662
IMR 3031	Winchester	CCI 200	37.0	2353	<b>41.0</b>	2657
IMR 4064	Winchester	CCI 200	40.0	2313	<b>44.0 C</b>	2623
Hodgdon H380	Winchester	CCI 250	45.0	2343	<b>49.0 C</b>	2603
IMR 4895	Winchester	CCI 200	38.0	2285	<b>42.0</b>	2602
Hodgdon H414	Winchester	CCI 250	44.0	2284	<b>48.0</b>	2597
Hodgdon H335	Winchester	CCI 250	37.0	2395	<b>41.0</b>	2592
Winchester 760	Winchester	CCI 250	45.0	2276	<b>49.0 C</b>	2554
Hodgdon H322	Winchester	CCI 200	34.0	2175	<b>38.0</b>	2437

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*