



307 Winchester

.308"	30
	SPFN Hot-Cor®
Weight (grains)	170
Ballistic Coefficient	0.298
Sectional Density	0.256
COAL Tested	2.530"
Speer Part No.	2041

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Winchester	CCI 200	40.5	2470	43.5	2669
Alliant AR-Comp	Winchester	CCI 200	38.0	2441	41.6	2613
IMR 8208 XBR	Winchester	CCI 200	38.5	2405	41.5	2583
IMR 4166	Winchester	Cci 200	38.0	2349	41.6	2524
Hodgdon H414	Winchester	CCI 250	41.0	2164	45.0 C	2504
Winchester 748	Winchester	CCI 250	38.0	2221	42.0	2494
Hodgdon BL-C(2)	Winchester	CCI 250	39.0	2265	43.0	2492
Hodgdon H380	Winchester	CCI 250	45.0	2200	49.0 C	2492
IMR 4064	Winchester	CCI 200	38.0	2293	42.0 C	2486
Hodgdon H335	Winchester	CCI 250	35.0	2141	39.0	2422
IMR 4320	Winchester	CCI 200	37.0	2104	41.0 C	2422
IMR 3031	Winchester	CCI 200	36.0	2128	40.0	2413
IMR 4895	Winchester	CCI 200	36.0	2064	44.0 C	2400

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load