



308 Norma Magnum

.308"	30 HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	3.185"
Speer Part No.	2005

NOTE: 125 gr TNT HP not recommended at these velocities.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4350	Norma	CCI 250	71.0	3137	75.0	3367
H380	Norma	CCI 250	66.0	3115	70.0	3362
IMR 4831	Norma	CCI 250	72.0	3097	76.0	3336
IMR 4064	Norma	CCI 250	60.0	3050	64.0	3304
Winchester 760	Norma	CCI 250	70.0	3038	74.0	3281
IMR 4320	Norma	CCI 250	60.0	2992	64.0	3257
Hodgdon H414	Norma	CCI 250	68.0	3006	72.0	3256
IMR 4895	Norma	CCI 250	58.0	2878	62.0	3122

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load