



308 Norma Magnum

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.090"	3.300"	3.300"	3.220"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4350	Norma	CCI 250	70.0	2975	74.0	3213
Hodgdon H380	Norma	CCI 250	64.0	2966	68.0	3209
Hodgdon H4831SC	Norma	CCI 250	71.0	2950	75.0	3175
IMR 4064	Norma	CCI 250	58.0	2910	62.0	3133
IMR 4895	Norma	CCI 250	58.0	2882	62.0	3125
IMR 4320	Norma	CCI 250	59.0	2859	63.0	3099
Hodgdon H414	Norma	CCI 250	62.0	2742	66.0	2984
Winchester 760	Norma	CCI 250	63.0	2753	67.0	2975

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load