



## 308 Norma Magnum

<b>.308"</b>	<b>30</b>
<b>Weight (grains)</b>	<b>Match BTHP</b>
<b>Ballistic Coefficient</b>	168
<b>Sectional Density</b>	0.534
<b>COAL Tested</b>	0.253
<b>Speer Part No.</b>	3.345"
	2040

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Accurate 3100</b>	Norma	CCI 250	67.0	2907	<b>71.0</b>	3090
<b>IMR 4831</b>	Norma	CCI 250	68.0	2861	<b>72.0</b>	3037
<b>IMR 4350</b>	Norma	CCI 250	65.0	2704	<b>69.0</b>	3035
<b>IMR 7828</b>	Norma	CCI 250	74.0	2833	<b>78.0</b>	3003
<b>IMR 4320</b>	Norma	CCI 250	55.0	2701	<b>59.0</b>	2923
<b>Winchester 760</b>	Norma	CCI 250	61.0	2710	<b>65.0</b>	2899
<b>IMR 4064</b>	Norma	CCI 250	56.0	2694	<b>60.0</b>	2893
<b>Accurate 8700</b>	Norma	CCI 250	80.0	2658	<b>84.0</b>	2804

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*