



308 Winchester

.308"	30
Weight (grains)	Plinker® SPRN
Ballistic Coefficient	100
Sectional Density	0.144
COAL Tested	0.151
Speer Part No.	2.360"
	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2460	IMI Commercial	CCI 250	47.0	3090	51.0 C	3403
Hodgdon H322	IMI Commercial	CCI 200	44.0	3011	48.0	3315
Vihtavuori N120	IMI Commercial	CCI 200	35.0	2867	39.0	3193
Hodgdon H4895	IMI Commercial	CCI 200	44.0	2806	48.0 C	3160
Winchester 748	IMI Commercial	CCI 250	48.0	2860	52.0 C	3116
IMR 4064	IMI Commercial	CCI 200	45.0	2853	49.0 C	3107
Alliant Reloder 7	IMI Commercial	CCI 200	37.0	2736	41.0	3047
IMR SR 4759 (reduced load)	IMI Commercial	CCI 200	16.0	1569	20.0	1949

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load