



308 Winchester

.308"	30
	TNT® HP
Weight (grains)	125
Ballistic Coefficient	0.341
Sectional Density	0.188
COAL Tested	2.635"
Speer Part No.	1986

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	44.2	2995	49.0 C	3231
Alliant Power Pro Varmint	Federal	Federal 210	43.9	2912	48.8	3196
Alliant Power Pro 1200-R	Federal	Federal 210	38.6	2918	42.9	3128
Alliant Reloder 10X	IMI Commercial	CCI 200	38.0	2845	42.0	3120
Alliant Reloder 15	IMI Commercial	CCI 200	46.0	2791	50.0 C	3108
Accurate 2460	IMI Commercial	CCI 250	44.0	2727	48.0 C	3107
IMR 4320	IMI Commercial	CCI 200	46.0	2695	50.0 C	3036
Accurate 2230	IMI Commercial	CCI 250	42.0	2654	46.0 C	3025
Winchester 748	IMI Commercial	CCI 250	46.0	2760	50.0 C	3006
Accurate 2520	IMI Commercial	CCI 250	44.0	2714	48.0 C	2989
Hodgdon H322	IMI Commercial	CCI 200	40.0	2669	44.0	2972
Vihtavuori N135	IMI Commercial	CCI 200	42.0	2661	46.0 C	2963
IMR 4895	IMI Commercial	CCI 200	42.0	2685	46.0 C	2957
Hodgdon Varget	IMI Commercial	CCI 200	45.0	2820	47.0 C	2954
IMR 4064	IMI Commercial	CCI 200	44.0	2643	48.0 C	2943
IMR 3031	IMI Commercial	CCI 200	41.0	2702	48.0 C	2942
IMR 4198 (reduced load)	IMI Commercial	CCI 200	25.0	1978	29.0	2201

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load