



## 308 Winchester

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	2.800"	2.800"	3.680"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	43.6	2491	47.8	2692
Alliant Reloder 15	IMI Commercial	CCI 200	41.0	2318	45.0 C	2643
Accurate 2460	IMI Commercial	CCI 250	39.0	2337	43.0	2633
Hodgdon Varget	IMI Commercial	CCI 200	40.0	2425	44.0	2620
Vihtavuori N150	IMI Commercial	CCI 200	41.0	2336	45.0 C	2602
Alliant AR-Comp	Federal	Federal 210	37.8	2412	41.5	2597
Winchester 748	IMI Commercial	CCI 250	41.0	2317	45.0	2581
Alliant Power Pro Varmint	Federal	Federal 210	37.9	2379	41.9	2574
IMR 4064	IMI Commercial	CCI 200	39.0	2313	43.0 C	2548
Winchester 760	IMI Commercial	CCI 250	44.0	2320	48.0 C	2527
Hodgdon H414	IMI Commercial	CCI 250	44.0	2202	48.0 C	2510
IMR 4320	IMI Commercial	CCI 200	40.0	2274	44.0	2504
Hodgdon H335	IMI Commercial	CCI 250	38.0	2296	42.0	2500
IMR 4166	Federal	Federal 210	36.0	2276	40.0	2485
Accurate 2520	IMI Commercial	CCI 250	37.0	2273	41.0	2475
Hodgdon H380	IMI Commercial	CCI 250	44.0	2162	48.0 C	2464
IMR 4895	IMI Commercial	CCI 200	37.0	2191	41.0	2441
IMR 4350	IMI Commercial	CCI 200	44.0	2163	48.0 C	2437
IMR 4198 (reduced load)	IMI Commercial	CCI 200	24.0	1589	28.0	1860

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load