



338-06 A-Square

.338"	338
	Grand Slam®
	SP/CANN
Weight (grains)	250
Ballistic Coefficient	0.436
Sectional Density	0.313
COAL Tested	3.340"
Speer Part No.	2408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Reformed Rem 35 Whelen	CCI 200	57.0	2377	61.0 C	2545
Hodgdon H4831	Reformed Rem 35 Whelen	CCI 200	57.5	2340	61.5 C	2505
IMR 4350	Reformed Rem 35 Whelen	CCI 200	53.5	2328	57.5	2504
Hodgdon H4350	Reformed Rem 35 Whelen	CCI 200	54.0	2327	58.0 C	2502
IMR 4831	Reformed Rem 35 Whelen	CCI 200	55.5	2321	59.5 C	2491
Vihtavuori N160	Reformed Rem 35 Whelen	CCI 200	54.0	2265	58.0	2486
Winchester 760	Reformed Rem 35 Whelen	CCI 200	52.5	2304	56.5	2480
Hodgdon H414	Reformed Rem 35 Whelen	CCI 200	53.0	2303	57.0	2479
IMR 4064	Reformed Rem 35 Whelen	CCI 200	46.5	2228	50.5	2423
Alliant Reloder 15	Reformed Rem 35 Whelen	CCI 200	46.0	2224	50.0	2421
Accurate 3100	Reformed Rem 35 Whelen	CCI 200	56.0	2256	60.0 C	2419
IMR 4320	Reformed Rem 35 Whelen	CCI 200	47.0	2223	51.0	2414

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load