



340 Weatherby Magnum

.338"	338
	Grand Slam® SP
Weight (grains)	250
Ballistic Coefficient	0.436
Sectional Density	0.313
COAL Tested	3.610"
Speer Part No.	2408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	76.2	2541	84.6 C	2865
IMR 7977	Federal	Federal 215	81.1	2504	90.2 C	2807
Vihtavuori N560	Federal	Federal 215	81.0	2668	85.0 C	2802
Alliant Reloder 23	Federal	Federal 215	74.4	2546	82.4 C	2797
Accurate MagPro	Federal	Federal 215	84.0	2669	88.0 C	2789
Alliant Reloder 19	Federal	Federal 215	79.0	2644	83.0	2788
Alliant Reloder 22	Federal	Federal 215	81.0	2634	85.0	2781
IMR 7828	Federal	Federal 215	81.0	2613	85.0 C	2747
IMR 4831	Federal	Federal 215	75.0	2607	79.0	2746
Hodgdon H4350	Federal	Federal 215	73.0	2608	77.0	2733
IMR 4350	Federal	Federal 215	73.0	2596	77.0	2731
Accurate 4350	Federal	Federal 215	75.0	2574	79.0 C	2720
Ramshot Magnum	Federal	Federal 215	86.0	2623	90.0 C	2711

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load