



speer®
bullets

357 Magnum (Rifle)

.357"	38 JHP	38 DCHP	38 JSP
Weight (grains)	158	158	158
Ballistic Coefficient	0.163	0.168	0.164
Sectional Density	0.177	0.177	0.177
COAL Tested	1.570"	1.575"	1.570"
Speer Part No.	4211	4215	4217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N110	Speer	CCI 500	13.5	1557	15.0	1745
Hodgdon H110	Speer	CCI 550	13.9	1459	15.5	1648
Alliant 2400	Speer	CCI 500	13.8	1517	14.8	1626
IMR 4227	Speer	CCI 500	15.0	1377	17.0 C	1583
Winchester 296	Speer	CCI 550	13.2	1317	14.7	1557
Accurate No. 9	Speer	CCI 500	12.3	1330	13.7	1543

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load