



## 35 Remington (Rifle)

<b>.358"</b>	<b>35</b>
<b>Weight (grains)</b>	<b>180</b>
<b>Ballistic Coefficient</b>	<b>0.236</b>
<b>Sectional Density</b>	<b>0.201</b>
<b>COAL Tested</b>	<b>2.470"</b>
<b>Speer Part No.</b>	<b>2435</b>

**35**  
**SPFN Hot-Cor®**

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Winchester	CCI 250	34.0	1971	<b>38.0</b>	2258
Alliant AR-Comp	Federal	Federal 210	33.6	2058	<b>36.7</b>	2211
Accurate 2015	Winchester	CCI 200	32.0	1953	<b>36.0</b>	2167
Alliant Power Pro Varmint	Federal	Federal 210	35.1	2026	<b>37.9</b>	2153
Hodgdon BL-C(2)	Winchester	CCI 250	31.0	1841	<b>35.0</b>	2123
Winchester 748	Winchester	CCI 250	38.0	1870	<b>42.0</b>	2097
Alliant Power Pro 1200-R	Federal	Federal 210	28.5	1973	<b>30.7</b>	2092
IMR 4895	Winchester	CCI 200	34.0	1820	<b>38.0</b>	2078
Vihtavuori N133	Winchester	CCI 200	31.0	1863	<b>35.0</b>	2077
Accurate LT-32	Federal	Federal 210	28.5	1946	<b>30.8</b>	2066
Hodgdon H414	Winchester	CCI 250	43.0	1858	<b>47.0</b>	2064
Hodgdon H380	Winchester	CCI 250	40.0	1816	<b>44.0</b>	2045
Alliant Reloder 10X	Federal	Federal 210	28.5	1968	<b>30.0</b>	2028
IMR 4320	Winchester	CCI 200	32.0	1733	<b>36.0</b>	2002
Alliant Reloder 7	Winchester	CCI 200	26.0	1681	<b>30.0</b>	1985
IMR SR 4759 (reduced load)	Winchester	CCI 200	18.0	1491	<b>20.0</b>	1653

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*