



35 Whelen

.358"	35 SPFN Hot-Cor®
Weight (grains)	220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	3.060"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Federal	Federal 210	57.8	2615	63.8 C	2826
Hodgdon CFE 223	Federal	Federal 210	61.0	2536	67.0 C	2788
Alliant Power Pro 2000-MR	Federal	Federal 210	62.2	2546	68.5 C	2786
Alliant AR-Comp	Federal	Federal 210	55.1	2557	61.0 C	2777
IMR 8208 XBR	Federal	Federal 210	52.8	2522	58.6	2741
Alliant Reloder 15	Remington	CCI 200	56.0	2445	60.0 C	2628
Winchester 748	Remington	CCI 250	59.0	2542	63.0 C	2588
Hodgdon H335	Remington	CCI 250	52.0	2312	56.0	2586
Accurate 2460	Remington	CCI 250	50.0	2390	54.0	2520
Vihtavuori N140	Remington	CCI 200	54.0	2330	58.0 C	2505
IMR 4451	Federal	Federal 210	57.1	2258	63.0 C	2504
IMR 3031	Remington	CCI 200	51.0	2294	55.0 C	2503
Hodgdon BL-C(2)	Remington	CCI 250	53.0	2371	57.0	2481
IMR 4064	Remington	CCI 200	52.0	2260	56.0 C	2468
Hodgdon H380	Remington	CCI 250	57.0	2300	61.0 C	2445
Accurate 2015	Remington	CCI 200	45.0	2252	49.0	2438
IMR 4895	Remington	CCI 200	49.0	2332	53.0	2400
Hodgdon H322	Remington	CCI 200	45.0	2236	49.0	2397
IMR 4320	Remington	CCI 200	50.0	2113	54.0	2298

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load