



## 35 Whelen

.358"	35 Spitzer SP Hot- Cor®
Weight (grains)	250
Ballistic Coefficient	0.422
Sectional Density	0.279
COAL Tested	3.340"
Speer Part No.	2453

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	60.0	2505	66.2 C	2709
Hodgdon CFE 223	Federal	Federal 210	57.9	2451	64.1	2664
Alliant Power Pro Varmint	Federal	Federal 210	53.5	2429	59.1	2617
Alliant AR-Comp	Federal	Federal 210	50.7	2379	56.1	2555
IMR 8208 XBR	Federal	Federal 210	50.0	2402	53.8	2525
IMR 4451	Federal	Federal 210	56.3	2236	62.1 C	2453
Hodgdon H335	Remington	CCI 250	49.0	2220	53.0	2408
Winchester 748	Remington	CCI 250	53.0	2296	57.0	2371
Accurate 2460	Remington	CCI 250	48.0	2209	52.0	2355
Hodgdon BL-C(2)	Remington	CCI 250	50.0	2178	54.0	2334
IMR 4064	Remington	CCI 200	49.0	2062	53.0	2331
Vihavuori N140	Remington	CCI 200	50.0	2144	54.0	2318
Hodgdon H380	Remington	CCI 250	55.0	2157	59.0 C	2306
Alliant Reloder 15	Remington	CCI 200	50.0	2148	54.0	2303
Accurate 2015	Remington	CCI 200	43.0	2174	47.0	2262
IMR 3031	Remington	CCI 200	47.0	2072	51.0	2262
Hodgdon H322	Remington	CCI 200	44.0	2134	48.0	2197
IMR 4895	Remington	CCI 200	45.0	2097	49.0	2156

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load