



375 Holland & Holland Magnum

.375"	375
	Grand Slam®
	SP/CANN
Weight (grains)	285
Ballistic Coefficient	0.354
Sectional Density	0.290
COAL Tested	3.560"
Speer Part No.	2473

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Federal	CCI 250	75.0	2606	79.0	2732
Hodgdon H414	Winchester	CCI 250	82.0	2645	84.0 C	2697
Accurate 4350	Winchester	CCI 250	77.0	2562	81.0 C	2694
Winchester 760	Winchester	CCI 250	83.0	2617	85.0 C	2658
IMR 4831	Winchester	CCI 250	79.0	2504	83.0 C	2649
IMR 4451	Federal	CCI 250	74.0	2503	79.0	2644
Hodgdon H4350	Winchester	CCI 250	75.0	2519	79.0 C	2615
IMR 4350	Winchester	CCI 250	75.0	2462	79.0 C	2575
Vihtavuori N160	Winchester	CCI 250	78.0	2531	80.0 C	2570
Hodgdon H4831SC	Winchester	CCI 250	82.0	2465	86.0 C	2561
IMR 4064	Winchester	CCI 250	64.0	2405	68.0	2552
Alliant Reloder 15	Winchester	CCI 250	65.0	2410	69.0	2533
Alliant AR-Comp	Federal	CCI 250	58.5	2391	64.0	2528
Accurate2700	Winchester	CCI 250	69.0	2392	73.0	2523
Hodgdon Varget	Winchester	CCI 250	64.0	2363	68.0	2510
Alliant Reloder 19	Winchester	CCI 250	78.0	2413	80.0 C	2456
IMR 4895	Winchester	CCI 250	60.0	2231	64.0	2400

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load