



375 Remington Ultra Magnum

.375"	375
	Grand Slam®
	SP/CANN
Weight (grains)	285
Ballistic Coefficient	0.354
Sectional Density	0.290
COAL Tested	3.580"
Speer Part No.	2473

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Remington	CCI 250	94.1	2731	104.0 C	3028
Alliant Reloder 19	Remington	CCI 250	94.1	2726	104.1 C	2996
IMR 7828	Remington	CCI 250	93.6	2677	103.7 C	2963
Alliant Reloder 23	Remington	CCI 250	91.4	2699	101.6 C	2961
Vihtavuori N560	Remington	CCI 250	91.7	2662	101.7	2953
Alliant Power Pro 4000-MR	Remington	CCI 250	86.9	2694	96.2	2949
Alliant Reloder 16	Remington	CCI 250	84.2	2673	93.5	2926
Hodgdon H4831	Remington	CCI 250	90.7	2656	100.4	2909
Alliant Reloder 17	Remington	CCI 250	80.7	2620	89.8	2909
Accurate 4350	Remington	CCI 250	85.6	2636	95.1	2909
Hodgdon H4350	Remington	CCI 250	83.7	2629	92.7	2884
Ramshot Hunter	Remington	CCI 250	83.2	2608	92.5	2862

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load