



416 Ruger

.416"	416
	Mag-Tip SP Hot-Cor®
Weight (grains)	350
Ballistic Coefficient	0.332
Sectional Density	0.289
COAL Tested	3.330"
Speer Part No.	2477

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Hornady	CCI 250	82.6	2503	91.4 C	2731
Winchester 760	Hornady	CCI 250	83.8	2504	93.1 C	2708
Alliant Reloder 17	Hornady	CCI 250	79.9	2438	88.5 C	2679
Hodgdon CFE 223	Hornady	CCI 250	80.6	2480	89.2	2669
Ramshot Big Game	Hornady	CCI 250	79.8	2479	87.4 C	2653
Accurate 2520	Hornady	CCI 250	73.4	2416	81.4	2642
Alliant Reloder 15	Hornady	CCI 250	73.8	2415	82.2	2619
Alliant Power Pro Varmint	Hornady	CCI 250	72.6	2390	80.6	2610
Vihtavuori N540	Hornady	CCI 250	74.0	2408	81.6	2596
Hodgdon Varget	Hornady	CCI 250	72.3	2393	79.9	2593
Alliant AR-Comp	Hornady	CCI 250	71.5	2368	79.6	2577
Hodgdon H335	Hornady	CCI 250	70.7	2366	78.5	2563

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load