



5.56x45mm NATO

.224"	22 GD
Weight (grains)	62
Ballistic Coefficient	0.310
Sectional Density	0.177
COAL Tested	2.260"
Speer Part No.	22462GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	CCI 41	27.3	2937	30.2 C	3180
Hodgdon CFE 223	Federal	CCI 41	25.1	2848	27.8	3089
Alliant Varmint	Federal	CCI 41	23.6	2794	26.2	3063
Ramshot X-Terminator	Federal	CCI 41	22.8	2780	25.3	3034
Hodgdon Varget	Federal	CCI 41	24.0	2794	26.6 C	3029
Accurate 2460	Federal	CCI 41	23.7	2789	26.2	3026
IMR 8208 XBR	Federal	CCI 41	23.0	2822	25.4	3024
Alliant Reloder 15	Federal	CCI 41	24.0	2731	26.6 C	3019
Alliant AR-Comp	Federal	CCI 41	22.3	2752	24.8	3013
IMR 4895	Federal	CCI 41	23.4	2695	25.9 C	2985
Hodgdon H335	Federal	CCI 41	22.5	2731	25.0	2975
Vihtavuori N540	Federal	CCI 41	24.1	2680	26.6	2971

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load