



6.5X55mm Swedish Mauser (Military Actions)

.264"	6.5mm
Weight (grains)	TNT@ HP
Ballistic Coefficient	90
Sectional Density	0.281
COAL Tested	0.184
Speer Part No.	2.850"
	1445

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Remington	CCI 250	48.0	3155	50.0	3278
Accurate 2700	Remington	CCI 250	47.0	3121	49.0	3244
Alliant Reloder 16	Federal	Federal 210	47.2	3152	49.0 C	3243
Alliant Reloder 17	Federal	Federal 210	45.1	2986	49.1	3240
IMR 4064	Remington	CCI 200	42.0	3105	44.0	3238
Hodgdon H4350	Remington	CCI 200	48.0	3098	50.0	3223
Alliant Reloder 15	Federal	Federal 210	40.1	2965	44.1	3215
Hodgdon Varget	Remington	CCI 200	41.0	3084	43.0	3193
IMR 4895	Remington	CCI 200	41.0	3051	43.0	3185
IMR 4350	Remington	CCI 200	48.0	3048	50.0	3178
IMR 3031	Remington	CCI 200	39.5	3038	41.5	3169
Accurate 4350	Remington	CCI 200	49.0	3029	51.0 C	3149
Alliant AR-Comp	Federal	Federal 210	36.0	2931	39.9	3143
Accurate 5744 (reduced load)	Remington	CCI 200	19.0	1841	21.0	2018

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load