



## 6.5X55mm Swedish Mauser (Strong Commercial Actions)

.264"	6.5mm Spitzer SP Hot- Cor®
Weight (grains)	140
Ballistic Coefficient	0.498
Sectional Density	0.287
COAL Tested	3.000"
Speer Part No.	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	37.7	2371	46.4	2744
Alliant Reloder 17	Federal	Federal 210	35.0	2309	42.1	2666
Alliant Power Pro 4000-MR	Federal	Federal 210	36.6	2368	43.2	2664
Alliant Reloder 23	Federal	Federal 210	35.6	2293	44.2	2658
Alliant Reloder 22	Remington	CCI 200	43.0	2579	45.0	2655
Alliant Reloder 19	Remington	CCI 200	43.0	2529	45.0	2616
Hodgdon H4831SC	Remington	CCI 200	41.0	2464	43.0	2558
IMR 4831	Remington	CCI 200	39.0	2467	41.0	2551
IMR 4350	Remington	CCI 200	39.0	2462	41.0	2545
Hodgdon H4350	Remington	CCI 200	38.0	2444	40.0	2531
Alliant Reloder 16	Federal	Federal 210	34.0	2330	38.4	2528
Hodgdon Varget	Remington	CCI 200	35.0	2390	37.0	2498
IMR 4064	Remington	CCI 200	34.0	2351	36.0	2462

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*