



## 6.5X55mm Swedish Mauser (Strong Commercial Actions)

<b>.264"</b>	<b>6.5mm</b>
	<b>TNT® HP</b>
<b>Weight (grains)</b>	90
<b>Ballistic Coefficient</b>	0.281
<b>Sectional Density</b>	0.184
<b>COAL Tested</b>	2.850"
<b>Speer Part No.</b>	1445

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Federal	Federal 210	45.1	2986	<b>52.3 C</b>	3443
Hodgdon Varget	Remington	CCI 200	45.0	3193	<b>47.0</b>	3410
Alliant Reloder 15	Federal	Federal 210	40.1	2965	<b>47.2</b>	3409
Hodgdon H414	Remington	CCI 250	50.0	3278	<b>52.0</b>	3401
Accurate 2700	Remington	CCI 250	49.0	3244	<b>51.0</b>	3385
IMR 4350	Remington	CCI 200	51.0	3243	<b>53.0 C</b>	3373
IMR 4064	Remington	CCI 200	44.0	3238	<b>46.0</b>	3371
Hodgdon H4350	Remington	CCI 200	50.0	3223	<b>52.0 C</b>	3348
Alliant AR-Comp	Federal	Federal 210	36.0	2931	<b>43.5</b>	3339
IMR 4895	Remington	CCI 200	43.0	3185	<b>45.0</b>	3320
IMR 3031	Remington	CCI 200	41.5	3169	<b>43.5</b>	3301
Alliant Reloder 16	Federal	Federal 210	47.2	3152	<b>49.0 C</b>	3243

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*