



6.8mm Remington SPC

.277"	270 Spitzer BTSP	270 Spitzer SP Hot-Cor®
Weight (grains)	130	130
Ballistic Coefficient	0.412	0.383
Sectional Density	0.242	0.242
COAL Tested	2.250"	2.250"
Speer Part No.	1458	1459

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	CCI 400	27.8	2466	29.8 C	2620
Alliant Power Pro Varmint	Federal	CCI 400	29.3	2483	31.0 C	2607
Winchester 748	Remington	CCI 200	29.0	2408	31.0 C	2547
Ramshot X-Terminator	Remington	CCI 200	27.0	2307	29.0 C	2450
Hodgdon H335	Remington	CCI 200	27.5	2261	29.5 C	2446
Alliant Reloder 10X	Remington	CCI 200	23.5	2276	25.5 C	2431
Hodgdon BL-C(2)	Remington	CCI 200	28.0	2245	30.0 C	2415
Ramshot TAC	Remington	CCI 200	26.5	2271	28.5	2399
Hodgdon Benchmark	Remington	CCI 200	25.0	2217	27.0 C	2391
Hodgdon H322	Remington	CCI 200	24.5	2223	26.5	2385
Accurate 2015	Remington	CCI 200	24.0	2165	26.0	2360
Vihtavuori N130	Remington	CCI 200	22.5	2185	24.5	2345
IMR 4198	Remington	CCI 200	20.0	2159	22.0	2317
Accurate 1680	Remington	CCI 200	20.5	2124	22.5	2262

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load