



6.8mm Remington SPC

.277"	27
	GD
Weight (grains)	90
Ballistic Coefficient	0.253
Sectional Density	0.168
COAL Tested	2.260"
Speer Part No.	27790GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE 223	Federal	GM205MAR	33.5	2873	37.2 C	3144
Accurate 2200	Federal	GM205MAR	27.3	2786	30.3	3053
Alliant Power Pro 1200-R	Federal	GM205MAR	27.4	2775	30.3	3025
Accurate 2230	Federal	GM205MAR	29.7	2822	32.6	3023
Hodgdon H335	Federal	GM205MAR	29.6	2767	32.8	3010
Alliant Reloder 10X	Federal	GM205MAR	26.4	2688	29.3	2976
Ramshot X-Terminator	Federal	GM205MAR	29.4	2777	32.6 C	2973
Hodgdon BENCHMARK	Federal	GM205MAR	28.5	2694	31.6	2972
Alliant Reloder 7	Federal	GM205MAR	25.2	2658	28.0	2899
Vihtavuori N120	Federal	GM205MAR	22.1	2599	24.7	2834

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load