



6mm Creedmoor

.243"	6mm
	HP
Weight (grains)	75
Ballistic Coefficient	0.192
Sectional Density	0.181
COAL Tested	2.550"
Speer Part No.	1205

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Hornady	CCI 200	42.1	3297	46.8	3656
Alliant Power Pro 2000-MR	Hornady	CCI 200	40.8	3349	45.3	3639
Ramshot Hunter	Hornady	CCI 200	46.7	3404	50.3 C	3620
Vihtavuori N550	Hornady	CCI 200	41.1	3300	45.6	3618
Winchester 760	Hornady	CCI 200	41.9	3293	46.5	3587
Hodgdon H4350	Hornady	CCI 200	43.4	3293	48.2 C	3578
Alliant Power Pro 4000-MR	Hornady	CCI 200	45.0	3303	48.5 C	3559
IMR 4451	Hornady	CCI 200	42.7	3225	46.8 C	3508
Alliant Reloder 16	Hornady	CCI 200	44.2	3361	45.4 C	3452
Accurate 4350	Hornady	CCI 200	44.5	3270	46.0 C	3377

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load