



6mm Creedmoor

.243"	6mm Spitzer SP Hot- Cor®
Weight (grains)	90
Ballistic Coefficient	0.365
Sectional Density	0.218
COAL Tested	2.700"
Speer Part No.	1217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Hornady	CCI 200	44.2	3142	49.0	3418
Alliant Power Pro 4000-MR	Hornady	CCI 200	41.9	3071	46.7	3362
Alliant Reloder 19	Hornady	CCI 200	43.2	3070	48.2	3361
Alliant Reloder 22	Hornady	CCI 200	42.7	3104	47.2	3356
Alliant Reloder 16	Hornady	CCI 200	40.6	3115	45.2	3348
Alliant Reloder 17	Hornady	CCI 200	39.2	3066	43.6	3341
Alliant Reloder 23	Hornady	CCI 200	42.9	3067	47.7 C	3318
Hodgdon 4350	Hornady	CCI 200	39.3	3044	43.3	3251
IMR 4831	Hornady	CCI 200	41.1	2950	45.6	3225
Winchester 760	Hornady	CCI 200	37.9	2999	42.1	3220
IMR 4451	Hornady	CCI 200	39.0	2962	43.2	3211
Accurate 4350	Hornady	CCI 200	36.0	2929	40.3	3167

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load