



6mm PPC

.243"	6mm
Weight (grains)	HP
Ballistic Coefficient	75
Sectional Density	0.192
COAL Tested	0.181
Speer Part No.	2.115"
	1205

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Sako	CCI BR4	26.0	2790	30.0 C	3257
Hodgdon BL-C(2)	Sako	CCI BR4	27.0	2931	29.0 C	3169
Hodgdon H322	Sako	CCI BR4	26.5	2910	28.5 C	3127
Alliant Reloder 7	Sako	CCI BR4	23.0	2791	25.0	3011
IMR 4198	Sako	CCI BR4	24.0	2620	26.0	2910
Winchester 748	Sako	CCI BR4	27.0	2634	29.0 C	2904
IMR 4895	Sako	CCI BR4	24.0	2508	26.0 C	2705

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load